ABSOLATION CONNECTING ELECTRONICS INDUSTRIES® International and Pa	<b>Dosition De</b> IPC, Bannock in-American c	<b>claration</b> burn, Illinois. A opyright conver	ll rights reserved u ntions.	nder both											sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				<ul> <li>Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mate</li> </ul>					faterials and M	ials and Mfg Information					
upplier Information																
Company name* Com			Company unique ID			Unique ID Authority					Respon	Response Date*				
onsemi											2023-0	2023-06-08				
ontact Name	ntact			Phone - Contact*					Email	Email - Contact*						
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA					Produ	Product-Env-Stewards@onsemi.com					
Authorized Representative* Title - R			itle - Representative			Phone - Representative*				Email	Email - Representative*					
roduct-Env-Stewards	Product Enviro Compliance				NA					Produ	Product-Env-Stewards@onsemi.com					
Requester Item Number	Requester Item Number Mfr Iter		n Number Mfr Item Name			Effective Da	ate V	Version     Manufacturing Site       PHG		te	Weight* 515.45		UOM	Unit Type		
	NCV74	NCV7462DQ0R2G CAN LIN 25		250mA LDO SBC		2023-06-08				PHG			mg	Each		
Ianufacturing Proccess Informa	ation						1		1			1		1	1	
Terminal Plating / Grid Array M	laterial '	Ferminal Base	Alloy	J-STD-020 MS	SL Rating	Peak Process		ss Body Temperature Max Time at Pea		Peak Tempera	Temperature Numbe		of Reflow Cyc	les		
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy 2		2		260		С		30		nds	3			
omments																
TTENTION: MSL 2 Rated item requir	es Dry Pack (	after electrical	test)													
or more information regarding materia	l composition	please refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed								
Directive 2015/863/EU amending RoHS Directive 2011/65/EU													
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of								
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all								
Exemption List Version	EL-2011/534/EU												
Declaration Signature													
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the								
Supplier Digital Signature Ra	stislav Drska	Le											

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	15.99	mg	Supplier	Silicon (Si)	7440-21-3		15.99	mg
Die Attach	2.86	mg		Epoxy resin	proprietary data		0.286	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.143	mg
			Supplier	Silver (Ag)	7440-22-4		2.288	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.143	mg
Lead Frame	172.4	mg	Supplier	Zinc (Zn)	7440-66-6		0.1724	mg
			Supplier	Iron (Fe)	7439-89-6		3.9652	mg
			Supplier	Copper (Cu)	7440-50-8		168.09	mg
			Supplier	Phosphorus (P)	7723-14-0		0.1724	mg
Mold Compound-Black	322.04	mg		Epoxy resin	proprietary data		16.102	mg
			Supplier	Phenolic Resin	Proprietary Data		6.4408	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		8.051	mg
			Supplier	Carbon Black (C)	1333-86-4		1.6102	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		289.836	mg
Plating	1.62	mg	Supplier	Palladium (Pd)	7440-05-3		0.08	mg
			В	Nickel (Ni)	7440-02-0		1.4599	mg
			Supplier	Gold (Au)	7440-57-5		0.08	mg
Wire Bond - Au	0.54	mg	Supplier	Gold (Au)	7440-57-5		0.54	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).