

## 500mA, 30V Schottky Barrier Diode

### FEATURES

- Designed for mounting on small surface
- Low Capacitance
- Low forward voltage drop
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

### APPLICATIONS

- Adapters
- For switching power supply
- Low stored charge
- Inverter

### MECHANICAL DATA

- Case: SOD-323F
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Polarity: Indicated by cathode band
- Weight: 4.60mg (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_F$	500	mA
$V_{RRM}$	30	V
$I_{FSM}$	5	A
$V_F$ at $I_F = 500\text{mA}$	0.47	V
$T_{J\text{MAX}}$	125	°C
Package	SOD-323F	
Configuration	Single die	



**SOD-323F**



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	B0530WS	UNIT
Marking code on the device		B3	
Repetitive peak reverse voltage	$V_{RRM}$	30	V
Forward current	$I_F$	500	mA
Non-repetitive peak forward surge current	$I_{FSM}$	5	A
	$t = 8.3\text{ms}$		
Junction temperature range	$T_J$	-65 to +125	°C
Storage temperature range	$T_{STG}$	-65 to +125	°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	LIMIT	UNIT
Junction-to-ambient thermal resistance	$R_{\theta JA}$	426	°C/W

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage <sup>(1)</sup>	$I_F = 100\text{mA}, T_J = 25^\circ\text{C}$	$V_F$	-	0.36	V
	$I_F = 500\text{mA}, T_J = 25^\circ\text{C}$		-	0.47	V
Reverse current @ rated $V_R$ <sup>(2)</sup>	$V_R = 15\text{V}, T_J = 25^\circ\text{C}$	$I_R$	-	80	$\mu\text{A}$
	$V_R = 20\text{V}, T_J = 25^\circ\text{C}$		-	100	$\mu\text{A}$
	$V_R = 30\text{V}, T_J = 25^\circ\text{C}$		-	500	$\mu\text{A}$
Junction capacitance	1MHz, $V_R = 0\text{V}$	$C_J$	-	160	pF

**Notes:**


1. Pulse test with  $PW = 0.3\text{ms}$
2. Pulse test with  $PW = 30\text{ms}$

<b>ORDERING INFORMATION</b>		
ORDERING CODE	PACKAGE	PACKING
B0530WS RRG	SOD-323F	3,000 / 7" Tape & Reel
B0530WS R9G	SOD-323F	10,000 / 13" Tape & Reel


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Typical Forward Characteristics**




**Fig.2 Forward Current Derating Curve**



**Fig.3 Admissible Power Dissipation Curve**




**Fig.4 Typical Junction Capacitance**



### CHARACTERISTICS CURVES



( $T_A = 25^\circ\text{C}$  unless otherwise noted)

**Fig.5 Typical Reverse Characteristics**



**PACKAGE OUTLINE DIMENSIONS**

**SOD-323F**



MARKING DIAGRAM

P/N = MARKING CODE

**SUGGESTED PAD LAYOUT**

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: EIAJ ED-7500A-1, SC-90.

4. MOLDED PLASTIC BODY LATERAL DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

5. DWG NO. REF: HQ2SD07-SOD323F-018 REV A.

## **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.