© Copy	rial Composition yright 2005. IPC, Bar tional and Pan-Ameri	nnockburn,	Illinois. All	l rights reserved u ions.	nder both	This docume level parts, t	ent is a declarat he declaration o	ion of the su encompasse	ibstances v s all lower	vithin the manufact level materials for	urer listed which the	item. Note: nanufacture	if the item is an as r has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type   http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
upplier Information															
Company name*			Company unique ID				Unique ID Authority					Response Date*			
onsemi												2023-06-08			
Contact Name T			Title - Contact				Phone - Contact*				Email ·	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email ·	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Nu	uester Item Number Mfr Item		m Number Mfr Item Name				Effective Date Version Manufacturing Si		lanufacturing Site		Weight*	UOM	Unit Type		
	FA	FAN48630UC50X 3MHZ		MHZ DC/DC Boost 1.5A		2023-06-08		Т	TW6		3.38704	mg	Each		
<b>Anufacturing Procces</b>	s Information														
Terminal Plating / C	Terminal Plating / Grid Array Material Terminal			Base Alloy J-STD-020 MSL Ra			Peak Process Body Temperature Max Time at Peak			ık Tempera	Temperature Number of Reflow Cycles				
SnAgCu CU			U Alloy 1				260 C 30			seconds 3					
omments															
vel 1 - maximum time at pea	ak temperature duri	ing solderii	ing is 10-30	seconds											
or more information regard	ing material compo	sition pleas	se refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl ohthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	2.40717	mg	Supplier	Silicon (Si)	7440-21-3		2.3978	mg		
			Supplier	Aluminum (Al)	7429-90-5		0.0094	mg		
Solder Ball	0.973411	mg	Supplier	Silver (Ag)	7440-22-4		0.0389	mg		
			Supplier	Tin (Sn)	7440-31-5		0.9296	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0049	mg		
Under Bump Metal	0.006459	mg	Supplier	Titanium (Ti)	7440-32-6		0.0052	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0012	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)