

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1205cs#pbf

(Engineering Calculation)

SOIC

(printed on: 2020-07-11 20:05:22)

**TOTAL MASS (g) : 0.154603**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.002178	1000000	14087.7226562		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.051070	975000	330330.59375		
		Iron (Fe)	7439-89-6	0.001257	24000	8130.51757812		
		Phosphorus (P)	7723-14-0	0.000016	300	103.491073608		
		Zinc (Zn)	7440-66-6	0.000037	700	239.323104858		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.052380</b>	<b>1000000</b>	<b>338803.875</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.002954	1000000	19105.125		
		<b>External Plating Total:</b>				<b>0.002954</b>	<b>1000000</b>	<b>19105.125</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000419	1000000	2710.17236328		
<b>Internal Plating Total:</b>				<b>0.000419</b>	<b>1000000</b>	<b>2710.17236328</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000726	750000	4695.90722656		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000242	250000	1565.30249023		
<b>Die Attach Total:</b>				<b>0.000968</b>	<b>1000000</b>	<b>6261.20996094</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.012389	130000	80134.4296875		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.079099	830000	511627.5		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.003336	35000	21577.8886719		
		Carbon Black (C)	1333-86-4	0.000477	5000	3085.32763672		
		<b>Encapsulation Total:</b>				<b>0.095301</b>	<b>1000000</b>	<b>616425.1875</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000403	1000000	2606.68164062		
					<b>TOTAL MASS (g) :</b>	<b>0.154603</b>		